



MEGAFLAT



MEGADYNE

Introduction to Megaflat

3

Polyurethane flat belts

Product range

4

Rubber flat belts

Product range

8

INTRODUCTION TO MEGAFLAT



MEGAFLAT belts are truly endless mandrel moulded without a single seam or splice. Special fabrics of Polyester, Polyamid, Aramide, Cotton yarn or Elastic yarn are manufactured in endless form on the most modern CNC knitting machines. The available coatings Polyurethane, Silicone and Natural Rubber are applied as an endless cover. This wide variety of basic materials and surface treatments guarantee the perfect belt for transmission and for conveying even at extreme speeds and in special environments.

MAIN FEATURES

- High flexibility
- Small pulley diameters
- Dimensional accuracy
- High speed
- Energy efficient
- Low noise and vibration
- Low maintenance
- Good chemical and ozone resistance
- High friction surface
- Uniform elongation values

MEGAFLAT is always a belt made exactly to customer requirements in endless form.

MAIN COMPONENTS OF MEGAFLAT BELTS

- **TENSILE REINFORCEMENT:**

Special fabrics are available with:

Elastic yarn, high elastic elongation from 4-10% for fixed shaft centre distances.

Polyamide, medium elastic from 0,5-1,5% for fixed shaft centre distances.

Polyester, low elastic elongation.

Cotton yarn, low elongation and low coefficient of friction.

Aramide, extremely low elongation and temperature resistance up to 280°.

- **COATINGS:**

Endless covers are available

Foamed Polyurethane, in colours yellow, grey, red and white, different hardness and thickness up to 10 mm, good coefficient of friction to paper


Neoprene Rubber, black with hardness approx. 75 Shore A, high resistance to abrasion, high coefficient of friction, rough on transport side and smooth on the reverse side

Silicones, in colours white, grey, red, blue, hardness approx. 30-35 ShA. High temperature resistant, FDA approved.



POLYURETHANE FLAT BELTS

PRODUCT RANGE

TYPE	P0	P102
		
Fabric	No fabric	Elastic fabric
Coating for drive or transport side	Standard: 50 ShA (+/-7) Special: 30-40 ShA (soft foam), 60-75 ShA (hard)	Standard: 50 ShA (+/-7) Special: 30-40 ShA (soft foam), 60-75 ShA (hard)
Coating revers side	No	Polyurethane/Silicone
Colour ⁽¹⁾	Yellow & Grey	Yellow & Grey
Antistatic	No	Possible

Coefficient of friction (μ)		
• Coated side smooth	0,4	0,4
• Fabric side rough	-	0,2

Breaking strength (N) per cm width in endless form	140	250
Pretension (N) recommended per cm width in endless form	-	10
Elongation (%) at pretension recommended per cm	4 - 8	4
Minimum recommended pulley diameter (mm)	8	25



Size (mm) ⁽²⁾		
• Length	210 - 2500	210 - 2500
• Width (length $\leq$ 460 mm)	6 - 330	6 - 330
• Width (length > 460 - 600 mm)	6 - 330	6 - 330
• Width (length > 600 - 750 mm)	6 - 550	6 - 600
• Width (length > 750 mm)	6 - 550	6 - 600
• Thickness	0,9	1,8 ⁽³⁾

Tolerances		
• Length (%)	+/-2,0	+/-2,0
• Width (mm)	+/-0,50	+/-0,50
• Thickness (mm)	+/-0,05	+/-0,05

Working temperature (intermittent)	-10°C / +60°C (+80)	-10°C / +60°C (+80)
Applications	Suitable for fixed center distance drive system like copying machines. Highly elastic.	Suitable for fixed center distance drive systems like machinery for paper transport. Elastic.

POLYURETHANE FLAT BELTS

PRODUCT RANGE

P105	P107	P108	P110
			
Polyester	Polyester/Cotton	Polyester/Cotton	Polyester
Standard: 50 ShA (+/-7) Special: 30-40 ShA (soft foam), 60-75 ShA (hard)	Standard: 50 ShA (+/-7) Special: 30-40 ShA (soft foam), 60-75 ShA (hard)	Standard: 50 ShA (+/-7) Special: 30-40 ShA (soft foam), 60-75 ShA (hard)	Standard: 50 ShA (+/-7) Special: 30-40 ShA (soft foam), 60-75 ShA (hard)
Polyurethane/Silicone	Polyurethane/Silicone	Polyurethane/Silicone	Polyurethane/Silicone
Yellow & Grey	Yellow & Grey	Yellow & Grey	Yellow & Grey
Possible	Possible	Possible	Possible

0,4	0,4	0,4	0,4
0,2	0,3	0,1	0,3

480	850	900	1250
30	250	200	150
0,8	0,8	1,2	0,8
8	8	8	12

210 - 3850	210 - 3850	210 - 3850	210 - 3850
6 - 330	6 - 330	6 - 330	6 - 330
6 - 330	6 - 330	6 - 330	6 - 330
6 - 600	6 - 600	6 - 600	6 - 600
6 - 600	6 - 600	6 - 600	6 - 600
0,8 ⁽³⁾	0,8 ⁽³⁾	0,8 ⁽³⁾	1,0 ⁽³⁾

+/-0,50	+/-0,50	+/-0,50	+/-0,50
+/-0,50	+/-0,50	+/-0,50	+/-0,50
+/-0,05	+/-0,05	+/-0,05	+/-0,05



-10°C / +60°C (+80)	-10°C / +60°C (+80)	-10°C / +60°C (+80)	-10°C / +60°C (+80)
Light transmission and conveyor belt. Flexible.	High flexible transmission belt for small bending diameter.	Suitable for knife edge transport. Low coefficient of friction on textile side. Thin, highly flexible band.	Suitable for flexible drive and transport systems like grinding machines. Very good running performance. Universal applications.

⁽¹⁾Additional colours on request - ⁽²⁾Additional dimensions on request

⁽³⁾Increase of thickness by about 0,3/0,5 mm for belts coated both sides

POLYURETHANE FLAT BELTS

PRODUCT RANGE

TYPE	P120	P155
		

Fabric	Polyester	Aramid/ Polyester
Coating for drive or transport side	Standard: 50 ShA (+/-7) Special: 30-40 ShA (soft foam), 60-75 ShA (hard)	Standard: 50 ShA (+/-7) Special: 30-40 ShA (soft foam), 60-75 ShA (hard)
Coating revers side	Polyurethane/Silicone	Polyurethane/Silicone
Colour ⁽¹⁾	Yellow & Grey	Yellow & Grey
Antistatic	Possible	Possible

Coefficient of friction (μ)		
• Coated side smooth	0,4	0,4
• Fabric side rough	0,2	0,2

Breaking strength (N) per cm width in endless form	3500	6500
Pretension (N) recommended per cm width in endless form	300	350
Elongation (%) at pretension recommended per cm	0,8	0,5
Minimum recommended pulley diameter (mm)	20	30


Size (mm) ⁽²⁾		
• Length	210 - 4300	210 - 4300
• Width (length $\leq$ 460 mm)	6 - 330	6 - 330
• Width (length > 460 - 600 mm)	6 - 330	6 - 330
• Width (length > 600 - 750 mm)	6 - 600	6 - 600
• Width (length > 750 mm)	6 - 600	6 - 600
• Thickness	1,5 ⁽³⁾	2,0 ⁽³⁾

Tolerances		
• Length (%)	+/-0,50	+/-1,0
• Width (mm)	+/-0,50	+/-0,50
• Thickness (mm)	+/-0,05	+/-0,05

Working temperature (intermittent)	-10°C / +60°C (+80)	-10°C / +60°C (+80)
Applications	Suitable for heavy drive conditions. Universal applications. Medium-duty drives.	Suitable for conveyor system. Extremely low elongation. Heavy-duty drives.

POLYURETHANE FLAT BELTS

PRODUCT RANGE

S108	S110	S120	S155
			
Polyester/Cotton	Polyester	Polyester	Aramid/Polyester
Silicone 30-35 ShA	Silicone 30-35 ShA	Silicone 30-35 ShA	Silicone 30-35 ShA
Polyurethane/Silicone	Polyurethane/Silicone	Polyurethane/Silicone	Polyurethane/Silicone
White & Grey	White & Grey	White & Grey	White & Grey
Possible	Possible	Possible	Possible
0,6	0,6	0,6	0,6
0,1	0,2	0,4	0,2
800	1000	3400	5900
180	125	350	400
0,8	0,8	0,8	0,5
8	12	20	25
210 - 3850	210 - 3850	210 - 4300	210 - 3800
6 - 330	6 - 330	6 - 330	6 - 330
6 - 330	6 - 330	6 - 330	6 - 330
6 - 600	6 - 600	6 - 600	6 - 600
6 - 600	6 - 600	6 - 600	6 - 600
0,8 ⁽³⁾	1,0 ⁽³⁾	1,5 ⁽³⁾	2,0 ⁽³⁾
+/-0,50	+/-0,50	+/-0,50	+/-1,0
+/-0,50	+/-0,50	+/-0,50	+/-0,50
+/-0,05	+/-0,05	+/-0,05	+/-0,05
-50°C / +120°C (+160)	-50°C / +150°C (+180)	-50°C / +150°C (+180)	-60°C / +280°C (+300)
Transport belt, heat and cold resistant. Knife edge transport. Food contact.	Transport belt, heat and cold resistant. Suitable for food transport.	Universal transport belt, also for drive applications.	Transport belt, high strength and high temperature extremes.

⁽¹⁾Additional colours on request - ⁽²⁾Additional dimensions on request

⁽³⁾Increase of thickness by about 0,3/0,5 mm for belts coated both sides

RUBBER FLAT BELTS

PRODUCT RANGE

TYPE	T75	T108	T110
			

Fabric	Polyester	Polyester/Cotton	Polyester
Coating for drive or transport side	Neoprene rough	Neoprene rough	Neoprene rough
Coating revers side	Neoprene smooth	Neoprene smooth	Neoprene smooth
Colour ⁽¹⁾	Black	Black	Black
Antistatic	Yes	Yes	Yes

Coefficient of friction (μ)			
• Coated side smooth	0,6	0,6	0,6
• Fabric side rough	0,5	0,5	0,5

Breaking strength (N) per cm width in endless form	1500	950	1750
Pretension (N) recommended per cm width in endless form	150	260	270
Elongation (%) at pretension recommended per cm	0,8	0,8	0,8
Minimum recommended pulley external diameter (mm)	6	10	15


Size (mm) ⁽²⁾			
• Length	200 - 3850	200 - 3850	200 - 3850
• Width (length $\leq$ 470 mm)	6 - 330	6 - 330	6 - 300
• Width (length > 470 - 600 mm)	6 - 430	6 - 430	6 - 430
• Width (length > 600 - 750 mm)	6 - 430	6 - 430	6 - 430
• Width (length > 750 mm)	6 - 430	6 - 430	6 - 430
• Thickness	0,5	0,65	0,9

Tolerances			
• Length (%) *(<= 600 mm: +/- 5mm)	+/-*0,50	+/-*0,50	+/-*0,50
• Width (mm) for cut belt	+/-0,50	+/-0,50	+/-0,50
• Thickness (mm)	+/-0,15	+/-0,15	+/-0,15

Working temperature	-30°C / +110°C	-25°C / +100°C	-25°C / +100°C
Applications	Suitable for light-load transmission or conveying. Drivers for office equipments.	Particularly suitable for applications in office equipment. Very flexible.	Suitable for universal applications and textile machines. High belt running speed.

RUBBER FLAT BELTS

PRODUCT RANGE

T120	T150	T155	T200
			
Polyester	Polyester	Aramid/ Polyester	Polyester
Neoprene rough	Neoprene rough	Neoprene rough	Neoprene rough
Neoprene smooth	Neoprene smooth	Neoprene smooth	Neoprene smooth
Black	Black	Black	Black
Yes	Yes	Yes	Yes
0,6	0,6	0,6	0,6
0,5	0,5	0,5	0,5
3450	3000	8000	4000
350	300	500	400
0,8	0,7	0,3	0,8
20	15	30	20
470- 3850	200 - 3850	470 - 3850	200 - 3850
6 - 330	6 - 330	6 - 330	6 - 330
6 - 430	6 - 430	6 - 430	6 - 430
6 - 430	6 - 430	6 - 430	6 - 430
6 - 430	6 - 430	6 - 430	6 - 430
1,4	0,9	1,6	1,1
+/-*0,5	+/-*0,5	+/-1,00	+/-*0,50
+/-0,50	+/-0,50	+/-0,50	+/-0,50
+/-0,15	+/-0,15	+/-0,15	+/-0,15
-25°C / +100°C	-25°C / +100°C	-25°C / +100°C	-30°C / +110°C
Suitable for medium-duty drives for wood or metal working.	Suitable for textile machinery. High belt running speed and medium torque drive	Suitable for low stretch demanding drive conditions. Heavy-duty drives.	Suitable for high torque, high speed drives such as machine tools.

NOTES



The data and information contained in the present catalogue are up-to-date to the date of the catalogue's printing. Megadyne Spa reserves the right to modify the specifications, performances and other information relating to the belts described in the present catalogue, at any time at its own discretion, without any prior notice. For updating refer to our web site www.megadynegroup.com.

Technical specifications, performances and other information provided in the present catalogue are indicative and do not bound Megadyne unless such specifications, performances or other information are expressly agreed in the agreement with the customer.

We also recommend to read carefully the following documents in our web site www.megadynegroup.com:

- Megadyne General Conditions of Sale (comprising the warranty)
- Theoretical Belt Life
- Drive Components: Storage, Installation, Maintenance and Troubleshooting Handbook - Belts standard use condition and temperature.

Copyright Notice: Megadyne Spa copyright. All rights reserved. Megadyne is and shall remain the owner of all rights on drawings, technical specifications and any other information contained in the present catalogue or otherwise communicated by Megadyne Spa to the customer. The customer shall not disclose such information to third parties or use such information for purposes different from the definition of the order to Megadyne Spa, unless upon prior written authorization of Megadyne.

AUSTRALIA

Melbourne

Phone +61 (03) 9763 6701
aussales@challengept.com

BELARUS

Minsk

Phone +375 17 2802486
Info.by@megadynegroup.com

BRASIL

Sorocaba

Phone +55 15 2101 7700
Info.br@megadynegroup.com

CANADA

Edmonton

Phone +1 780 461 4400
Info.ca@megadynegroup.com

Montreal

Phone +1 514 31 2341
Info.ca@megadynegroup.com

Toronto

Phone +1 905 602 4400
Info.ca@megadynegroup.com

CHINA

Beijing

Phone +86 10 8150 7478
info.cn@megadynegroup.com

Foshan

Phone +86 757 8381 5530
info.cn@megadynegroup.com

Ningbo*

Phone +86 574 8650 5008
info.cn@megadynegroup.com

Phone +86 574 8833 4378
sales@challengept.com

Qingdao*

Phone +86 532 8658 0951
info.cn@megadynegroup.com

Shanghai

Phone +86 21 5447 1473
info.cn@megadynegroup.com

Xi'an

Phone +86 29 86358108
info.cn@megadynegroup.com

COLOMBIA

Bogotá

Phone + 57 (1) 471 0503
Phone + 57 (1) 893 9890
Info.co@megadynegroup.com

Cartagena

Phone + 57 (5) 669 3604
Info.co@megadynegroup.com

CZECH REPUBLIC

Prague

Phone +420 2 8481 7181
Info.cz@megadynegroup.com

FRANCE

Paris

Phone +33 1 6079 8200
info.fr@megadynegroup.com

St. Jean De Maurienne*

info.fr@megadynegroup.com

GERMANY

Borchen

Phone +49 5251 8735 0
info.de@megadynegroup.com

Elchingen*

info.de@megadynegroup.com

HUNGARY

Budapest

Phone +36 23 428 628
info.hu@megadynegroup.com

INDIA

Chennai*

Phone +91 98841 81175
info.in@megadynegroup.com

IRELAND

Dublin

Phone +353 1 456 6311
ireland@challengept.com

ISRAEL

Caesarea

Phone +972 4 6371485
sales@megabelt.co.il

ITALY

Turin*

Phone +39 011 926 8052
info@megadynegroup.com

Pescara*

Phone +39 085 9700547
info.it@megadynegroup.com

Venice

Phone +39 041 929 367
info.it@megadynegroup.com

MEXICO

Mexico C.P.

Phone +52 55 5587 3680
info.mx@megadynegroup.com

PERU

Lima

Phone + 51 713 0069
info.pe@megadynegroup.com

POLAND

Bielsko Biala

Phone + 48 32 447 7179
info.pl@megadynegroup.com

Bydgoszcz*

info.pl@megadynegroup.com

SOUTH AFRICA

Johannesburg

Phone + 27 (0) 12 661 1652
info.za@megadynegroup.com

Phone + 27 (0) 11 3976115
sasales@challengept.com

Cape Town

Phone +27 (0)21 9820772
info.za@megadynegroup.com

SPAIN

Vilanova*

Phone +34 93 811 5450
info.es@megadynegroup.com

SWEDEN

Kristianstad

Phone +46 10 1309600
info.se@megadynegroup.com

THAILAND

Bangkok

Phone +66 966 207648
info.th@megadynegroup.com

TURKEY

Izmir

Phone +90 232 877 07 00
info.tr@megadynegroup.com

U.K.

Birmingham

Phone +44 1384 215 021
info.uk@megadynegroup.com

Wolverhampton

Phone +44 (0) 1902 866116
uksales@challengept.com

U.S.A

California

Phone +1 323 265 8061
info.us@megadynegroup.com

Florida

Phone +1 813 241 4111
info.us@megadynegroup.com

Georgia*

info.us@megadynegroup.com

Illinois

Phone +1 630 752 0600
info.us@megadynegroup.com

New Jersey Americas HQ

Phone +1 973 227 4904
info.us@megadynegroup.com

North Carolina*

info.us@megadynegroup.com

Oregon

Phone +1 503 231 7224
info.us@megadynegroup.com

Texas

Phone +1 972 438 6992
info.us@megadynegroup.com

HEADQUARTERS

ITALY Turin

Via S. Lucia, 114
10075 Mathi (Torino)
Phone +39 011 926 8052
info@megadynegroup.com

www.megadynegroup.com



MEGADYNE



* Manufacturing locations